

EV-LFP72-200, 72V200AH LiFePO4 Battery Specification

Characteristic		Photo for reference
Nominal voltage (V)	72 V (23S)	 www.BonnenBatteries.com
Nominal capacity (Ah)	200 Ah	
Total energy (Kwh)	14.4 Kwh	
Voltage range (V)	57.5-83.95V	
Standard charging current (A)	70A	
Max charging current (A)	200 A	
Standard discharging current (A)	200 A	
Max discharging current (A)	350 A (10s)	
BMS power consumption (W)	<1.5W	
Design life	More than 10 years	
Cycle life	More than 4000 cycles at 80% DOD	
Dimensions & Weight		
Dimension (mm)	910x400x294	
(can be customize)	(WxDxH)	
System weight (kg)	133.5	
Environment		
Operation thermal ambient (°C)	Charge: 0°C ~ 40°C Discharge: -20°C ~ 55°C	
Storage temp	<1month: -20°C ~ 45°C <3month: -20°C ~ 40°C 3-6month: -20°C ~ 25°C	
Storage humidity	<80%	
Protection grade	IP65	
Protection		
Over-current protection	YES	
Over-voltage protection	YES	
Under-voltage protection	YES	
Over-temperature protection	YES	
Short-circuit protection	YES	

EV batteries

Golf cart batteries

Low Speed vehicle batteries

Tourist batteries

Specialized Services

Address

Lugu International Industrial park, Changsha
 High-tech Development Zone, Changsha,
 Hunan, China

e-mail: info@bonnenbatteries.com