

EM-LFP96-100, 96V 100AH, LiFePO4 Battery Specification

Characteristic		Photo for reference
Nominal voltage (V)	96 V	 www.BonnenBatteries.com
Nominal capacity (Ah)	100 Ah	
Total energy (Kwh)	9.6 Kwh	
Voltage range (V)	75-109.5V	
Standard charging current (A)	30 A	
Max charging current (A)	100 A	
Standard discharging current (A)	100 A	
Max discharging current (A)	300 A (5s)	
BMS power consumption (W)	<1.5W	
Design life	More than 10 years	
Cycle life	More than 4000 cycles at 80% DOD	
Dimensions & Weight		 www.BonnenBatteries.com
Dimension (mm)	Custom	
(can be customize)	720*442*240 mm	
System weight (kg)	About 80	
Environment		
Operation thermal ambient (°C)	Charge: 0°C ~ 40°C Discharge: -20°C ~ 55°C	
Storage temp	<1month: -20°C ~ 45°C <3month: -20°C ~ 40°C 3-6month: -20°C ~ 25°C	
Storage humidity	<80%	
Protection grade	IP67	
Protection		
Over-current protection	YES	
Over-voltage protection	YES	
Under-voltage protection	YES	
Over-temperature protection	YES	
Short-circuit protection	YES	

Outboard Motors

Inboard Motors

E-boats

Tender

Yacht

Address

 Xiangfeng Science Industrial Park,
 Changsha City,
 Hunan Province, China

 e-mail: info@bonnenbatteries.com